


Tile Tech Inc.
Paving America one step at a time!


National Distribution
Toll Free: 888-380-5575

Tel: 213-380-5560
Fax: 213-380-5561



UNI-COUPLER™ PEDESTAL SYSTEM

COMPONENT ASSEMBLY INSTRUCTIONS.
HEIGHT ADJUSTMENT FROM 2-1/4" TO 24" & SLOPE ADJUSTMENT
FROM 0% TO 4%



PRODUCT CHARACTERISTICS:

- ADJUSTABLE HEIGHT FROM 2-1/4" TO 24" WITH USE OF 4" UNI-COUPLER.
- SELF-LEVELING CAP AUTOMATICALLY ADJUST SLOPE FROM 0% TO 4%.
- SCREW ADJUSTABLE WHILE PEDESTALS ARE LOADED FOR FINAL HEIGHT ADJUSTMENT OF 1-1/2"
- RESISTANT & IMPERVIOUS TO FREEZE-THAW, WATER, MOLD, ACID & ULTRAVIOLET DETERIORATION.
- RESISTANT TO TEMPERATURES BETWEEN -22°F AND +250°F.
- LARGE FOOT PRINT SPREADS WEIGHT OVER ROOFING MEMBRANE AND SUBSTRATE
- BUFFER PADS PROVIDE NOISE DAMPENING, SLIP RESISTANCE AND PROTECTION TO ROOFING MEMBRANE AND SUBSTRATE.
- MAXIMUM DESIGN CAPACITY OF 2,000 LBS PER PEDESTAL.

GENERAL NOTES: APPLY TO ALL OF THE ABOVE PRODUCTS

1. INSTALLATION MUST BE COMPLETED IN ACCORDANCE WITH TILE TECH PAVERS PRODUCT SPECIFICATIONS.
2. DRAWING NOT TO SCALE.
3. USE OF BUFFER PADS IS MANDATORY.
4. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.TILETECHPAVERS.com